



LANE REGIONAL AIR PROTECTION AGENCY
1010 Main Street, Springfield, Oregon 97477
(541) 736-1056

STANDARD AIR CONTAMINANT DISCHARGE PERMIT (ACDP)

Issued in accordance with provisions of Title 37, Lane Regional Air Protection Agency's Rules and Regulations, and based on the land use compatibility findings included in the permit record.

Issued To:
McFarland Cascade Pole and Lumber Company
P.O. Box 1496
Tacoma, Washington 98401-1496

Information Relied Upon:
Application Number: 69780
Date Received: August 21, 2023

Land Use Compatibility Statement:
From: City of Eugene
Dated: February 27, 1998

Facility Location:
90049 Highway 99 North
Eugene, Oregon 97402

Fee Basis – Title 37, Table 1:
Part B: 73. Wood preserving
Part C: 3. All sources electing to maintain the source's netting basis

Permit Number: 205108
Permit Type: Standard
Primary SIC: 2491 – Wood Preserving
Secondary SIC: NA
Issuance Date: November 10, 2020
Expiration Date: November 10, 2025
Modified Date: [Insert Date]

DRAFT

Issued

By: _____
Susannah Sbragia, Acting Interim Director

Effective

Date: _____

ADDENDUM NO. 1
NON-PSD/NSR SIMPLE TECHNICAL PERMIT MODIFICATION

In accordance with 37-0066(4)(b)(A) of LRAPA's Rules and Regulations, Standard Air Contaminant Discharge Permit No. 205108 is hereby amended to add one (1) natural gas-fired boiler. LRAPA has performing Agency-initiated changes to the permit including changing the PSELs from Generic PSELs to site specific PSELs and removal of federal standards that no longer apply. The review report contains additional details on the changes.

Permitted Activities

1. Until this permit expires or is revoked, the permittee is herewith allowed to discharge air contaminants only in accordance with the permit application and the requirements, limitations, and conditions contained in this permit. This specific listing of requirements, limitations, and conditions does not relieve the permittee from complying with all other rules of Lane Regional Air Protection Agency (LRAPA).

Emission Unit Description

2. Emission units regulated by this permit are the following:

Emission Unit ID	Description	Pollution Control Device (PCD ID)	Installed / Last Modified
Significant Emission Units			
EU-1	Oil-based Wood Preserving including: <ul style="list-style-type: none"> • 4 Retorts • Storage and Work Tanks • Cooling Tower • Fugitive Sources 	None	Retort 1 - 1994 Retort 2 - 1994 Retort 3 - 1995 Retort 4 - 1996
B-1	Boiler (14.7 MMBtu/hr) – Gas-Fired with No. 2 Fuel Oil Backup	None	1995
B-2	Boiler (16.8 MMBtu/hr) – Gas-Fired Only	None	2023

Plant Site Emission Limits (PSELS)

3. Total emissions from all sources located at the facility must not exceed the PSELS listed below. Each PSEL applies to any 12 consecutive calendar month period. [LRAPA 42-0041, 42-0080(3) and OAR 340-222-0041(3)]

Pollutant	PSEL (tons per year)
PM	de minimis
PM ₁₀	de minimis
PM _{2.5}	de minimis
CO	13
NO _x	11
SO ₂	de minimis
VOC	7.4
GHG (CO ₂ eq)	15,906

4. Any changes in operation that may increase the emissions above the PSELS must be approved by LRAPA. Failure to do so may result in enforcement actions being taken by LRAPA. [LRAPA 42-0080]

PSEL Monitoring and Compliance

5. By the 15th working day of each month, the permittee must determine compliance with the previous consecutive 12 calendar month PSELS. Compliance with the PSELS are determined for each consecutive 12-month period based on the following calculation for each pollutant: [LRAPA 34-016 and 42-0080(4)(c)]

$$E = \sum_{i=1}^{12} \frac{EF \cdot P_i}{2000}$$

Where:

E = Emissions in tons per year;

Σ = Symbol representing “summation of”;

I = Month, beginning with the most recent, summing for 12 preceding, consecutive calendar months;

EF = Pollutant emission factor in Condition 6; and

P = Process production or parameter.

- The permittee must use the following emission factors for calculating pollutant emissions, unless alternative emission factors are approved by LRAPA. The permittee may request the use of alternative emission factors provided they are based on actual test data or other documentation (e.g., AP-42 compilation of emission factors). The use of alternative emission factors is not allowed until the alternative emission factors have been reviewed and approved by LRAPA using procedures in title 34 and/or title 37, as appropriate. [LRAPA 34-016(1) and 42-0080(4)(c)]

EU ID	Emission Unit	Pollutant	Emission Factor	Units
EU-1	Wood Treatment	VOC	2.24E-3	Lb/cubic feet
B-1	Boilers – Natural Gas	NO _x	100	Lb/MMCF
B-2		CO	84	Lb/MMCF
		VOC	5.5	Lb/MMCF
		GHG (CO ₂ eq.)	117	Lb/MMBtu
B-2	Boilers – Fuel Oil	NO _x	20	Lb/1000 gallons
		CO	5	Lb/1000 gallons
		VOC	0.2	Lb/1000 gallons
		GHG (CO ₂ eq.)	164	Lb/MMBtu

Production Limitations

- The permittee must not treat more than 6,000,000 cubic feet of product for each 12-month rolling period or exceed 2,400 charges for each 12-month rolling period. [LRAPA 34-016 and 42-0080]
- The permittee must not allow more than two (2) retort door openings in any 60-minute period. [LRAPA 32-007]
- The sulfur content of the ASTM Grade 2 fuel oil combusted by Emission Unit B-1 must not exceed 0.5 percent by weight. [LRAPA 32-065(2)(b)]

Nuisance Emission Requirements

- The permittee must not cause or allow air contaminants from any source subject to regulation by LRAPA to cause a nuisance. [LRAPA 49-010(1)]
- The permittee must not cause or permit the emission of particulate matter which is larger than 250 microns in size at sufficient duration or quantity as to create an observable deposition upon the real property of another person. [LRAPA 32-055]
- The permittee must not discharge from any source whatsoever such quantities of air contaminants which cause injury or damage to any persons, the public, business or property; such determination to be made by LRAPA. [LRAPA 32-090(1)]
- To demonstrate compliance with Conditions 10 through 12, the permittee must provide LRAPA with written notification within five (5) days of all nuisance complaints received by the permittee during the operation of the facility and maintain a log of each nuisance complaint received by the

permittee during the operation of the facility. Documentation must include date of contact, time of observed nuisance condition, description of nuisance condition, location of complainant, status of plant operation during the observed period, and time of response to complainant. A facility representative must immediately (within one (1) hour during normal business hours) investigate the condition following the receipt of the nuisance complaint and a plant representative must provide a response to the complainant within 24 hours, if possible, but no later than five (5) business days. [LRAPA 34-016(1)]

General Emission Limitations

14. The permittee must not cause, suffer, allow or permit any materials to be handled, transported, or stored; or a building, its appurtenances, or a road to be used, constructed, altered, repaired or demolished; or any equipment to be operated, without taking reasonable precautions to prevent particulate matter from becoming airborne. Such reasonable precautions must include, but are not limited to the following: [LRAPA 48-015(1)]
 - 14.a. Use, where possible, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land;
 - 14.b. Application of water or other suitable chemicals on unpaved roads, materials stockpiles, and other surfaces which can create airborne dusts;
 - 14.c. Full or partial enclosure of materials stockpiles in cases where application of water or other suitable chemicals is not sufficient to prevent particulate matter from becoming airborne;
 - 14.d. Installation and use of hoods, fans, and fabric filters to enclose and vent the handling of dusty materials;
 - 14.e. Adequate containment during sandblasting or other similar operations;
 - 14.f. The covering of moving, open bodied trucks transporting materials likely to become airborne;
 - 14.g. The prompt removal from paved streets of earth or other material which does or may become airborne.
15. The permittee must demonstrate compliance with Condition 14 by conducting a fugitive emissions survey. At least once each month for a minimum period of 30 minutes, the permittee must visually survey the facility using EPA Method 22 for any sources of fugitive emissions. For purposes of this condition, fugitive emissions are visible emissions that leave the plant site boundary for a period or periods totaling more than 18 seconds in a six-minute period. The person conducting EPA Method 22 does not have to be EPA Method 9 certified. However, the individual conducting EPA Method 22 should be familiar with the procedures of EPA Method 9, including using the proper location to observe visible emissions. [LRAPA 34-016(1) and LRAPA 48-015(2)&(3)]
 - 15.a. If sources of fugitive emissions are identified that leave the plant site boundary for a period or periods totaling more than 18 seconds in a six-minute period, the permittee must immediately take corrective action to minimize the fugitive emissions, including but not limited to those actions identified in Condition 14. After taking corrective action, the permittee must conduct another fugitive emissions survey using EPA Method 22 within 24 hours of the previous fugitive emissions survey.
 - 15.b. If the fugitive emissions survey performed within 24 hours of the previous fugitive emissions survey detects visible emissions that leave the plant site boundary for a period or periods totaling more than 18 seconds in a six-minute period, the permittee must immediately notify LRAPA. LRAPA may require the facility to develop and implement a Fugitive Emission Control Plan to prevent any visible emissions from leaving the plant site boundary.
16. The permittee must not emit or allow to be emitted any visible emissions from any source that equal or exceed an average of 20 percent opacity for a period or periods aggregating more than three (3) minutes in any one (1) hour. [LRAPA 32-010(3)]
17. For any air contaminant sources installed, constructed or modified on or after June 1, 1970 but prior to April 16, 2015, for which there are no representative compliance source test results prior to

April 16, 2015, the permittee must not cause, suffer, allow, or permit particulate matter emissions in excess of 0.14 grains per dry standard cubic foot. [LRAPA 32-015(2)(b)(B) and 32-030(1)(b)]

18. For any air contaminant source installed, constructed or modified after April 16, 2015, the permittee must not cause, suffer, allow, or permit particulate matter emissions in excess of 0.10 grains per dry standard cubic foot. [LRAPA 32-015(2)(c) and 32-030(2)]
19. For Emission Unit EU-1, the permittee must not cause, suffer, allow or permit the emissions of particulate matter in any one (1) hour from any non-fuel burning process in excess of the amount shown in LRAPA 32-8010, for the process weight allocated to the process. [LRAPA 32-045(1)]
20. The permittee must demonstrate compliance with Conditions 16 through 19 by performing a visible emissions survey of the plant. At least once each month for a minimum period of 30 minutes, the permittee must visually survey the plant using EPA Method 22 for any sources of visible emissions. For the purposes of this condition, visible emissions requiring action are considered to be any visible emissions that do not result from mobile or fugitive sources and are not the result of condensed water vapor. The person conducting the EPA Method 22 does not have to be EPA Method 9 certified. However, the individual conducting the EPA Method 22 should be familiar with the procedures of EPA Method 9, including using the proper location to observe visible emissions. [LRAPA 34-016(1)]
 - 20.a. If visible emissions are observed using EPA Method 22, the permittee must take corrective action to eliminate the visible emissions within one (1) hour of finishing the visible emissions survey. After taking corrective action to eliminate the visible emissions, the permittee must conduct another visible emissions survey using EPA Method 22 within 24 hours of the previous visible emissions survey.
 - 20.b. If the visible emissions survey performed within 24 hours of the previous visible emissions survey detects visible emissions from the same source(s), the permittee is required to perform a Modified EPA Method 9 on the source(s) of visible emissions. If the results of the Modified EPA Method 9 are in compliance with Condition 16, no further action is required beyond the recordkeeping required in Condition 21. If the results of the Modified EPA Method 9 are not in compliance with Condition 16, the permittee must immediately contact LRAPA. [LRAPA 34-016(1)]
21. The permittee must keep documentation of all visible and fugitive emissions surveys required by Conditions 15 and 20. For all corrective actions taken, the permittee must record the date, time, person or entity performing the corrective action, and the corrective actions taken, as applicable. [LRAPA 34-016(1)]
22. For Emission Unit EU-1, the permittee must also prepare and update, as necessary, an Operation and Maintenance Plan (O&M Plan). The O&M Plan must include requirements for the proper operation and maintenance of all control devices at the facility, including but not limited to the fiber bed filters. The permittee must submit a copy of the O&M Plan to LRAPA for review upon request. If LRAPA determines the O&M Plan is deficient, LRAPA may require the permittee to amend the plan. For each emission control device, the O&M Plan must, at a minimum, identify the frequency of inspections and procedures for documenting each inspection. Documentation of each inspection must include the date and time of each inspection, the person or entity performing the inspection, identification of the equipment inspected, the results of each inspection, and any actions taken if repairs or maintenance are necessary. [LRAPA 32-007(1)(b)]

Conditions Specific to Emission Units B-1 and B-2

Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units (NSPS) – 40 CFR 60 Subpart Dc

23. For Emission Unit B-1, the permittee must combust oil that contains no more than 0.5 weight

- percent sulfur. [LRAPA 46-535(3)(e) and 40 CFR 60.42c(d)]
24. For Emission Unit B-1, the permittee must demonstrate compliance with the fuel oil sulfur limits in Condition 23 based on a certification from the fuel supplier as described in Condition 25. [LRAPA 46-535(3)(e) and 40 CFR 60.42c(h)(1)]
 25. For Emission Unit B-1, fuel supplier certification must include the following information: . [LRAPA 46-535(3)(e) and 40 CFR 60.48c(f)(1)]
 - 25.a. For distillate oil:
 - 25.a.i. The name of the oil supplier;
 - 25.a.ii. A statement from the oil supplier that the oil complies with the specifications under the definition of distillate oil in 40 CFR 60.41c; and
 - 25.a.iii. The sulfur content or maximum sulfur content of the oil.
 26. For Emission Unit B-1, which is subject to fuel oil sulfur limits, the permittee must keep records and submit reports to LRAPA, including the following information: [LRAPA 46-535(3)(e) and 40 CFR 60.48c(e)]
 - 26.a. Calendar dates covered in the reporting period. [LRAPA 46-535(3)(e) and 40 CFR 60.48c(e)(1)]
 - 26.b. Records of fuel supplier certification as described in Condition 25. In addition to records of fuel supplier certifications, the report must include a certified statement signed by the permittee that the records of fuel supplier certifications submitted represent all of the fuel combusted during the reporting period. [LRAPA 46-535(3)(e) and 40 CFR 60.48c(e)(11)]
 27. For Emission Unit B-1, the reporting period for reports required under Condition 26 is each six month period January 1 to June 30 and July 1 to December 31. All reports must be submitted to LRAPA and must be postmarked by the 45th day following the end of the reporting period. [LRAPA 46-535(3)(e), 40 CFR 60.19(c) and 40 CFR 60.48c(j)]
 28. For Emission Units B-1 and B-2, the permittee must record and maintain records of the amount of each fuel combusted by each boiler during each calendar month. [LRAPA 46-535(3)(e) and 40 CFR 60.48c(g)(2)]
 29. All records required under Conditions 23 through 28 must be maintained by the permittee for a period of two years following the date of such record. [LRAPA 46-535(3)(e) and 40 CFR 60.48c(i)]
- National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boiler Area Sources – 40 CFR 63 Subpart JJJJJJ (6J)***
30. The permittee must only combust fuel oil in Emission Unit B-1 during periods of gas curtailment, gas supply interruption, startups, or for periodic testing, maintenance, or operator training. Periodic testing, maintenance, or operator training on fuel oil must not exceed a combined total of 48 hours during any calendar year. [LRAPA 44-150(5)(jjjjj) and 40 CFR 63.11237]
 31. The permittee keep and maintain records of the total number of hours that the Emission Unit B-1 combusts fuel oil each month. [LRAPA 34-016(1)]
- National Emission Standards for Hazardous Air Pollutants for Wood Preserving Area Sources – 40 CFR 63 Subpart QQQQQQ (6Q)***
32. The permittee must keep and maintain records that document that the facility does not use any wood preservative containing chromium, arsenic, dioxins, or methylene chloride. [LRAPA 44-150(5)(jjjjj) and 40 CFR 63.11237]

Monitoring and Recordkeeping Requirements

33. The permittee must keep and maintain records for a period of at least five (5) years from the date of entry of the following information: [LRAPA 34-016(1)&(5) and 42-0080(3)]

Activity	Units	Minimum Recording Frequency
PSEL Recordkeeping		
Date, time, type and quantity of material removed from the retorts.	NA	Each occurrence
Production of treated wood.	Cubic feet	Monthly and 12 month rolling
Date and time of retort door openings.	NA	Per Opening
Number of charges.	NA	Monthly and 12 month rolling
Name, type and quantity used for all chemicals used in the wood treatment process.	NA	Annually
The amount of natural gas combusted by each boiler.	Therms or MMCF	Monthly
The amount of fuel oil combusted by Emission Unit B-1.	Gallons	Monthly
General Recordkeeping		
Log of nuisance complaints.	NA	Upon receipt of complaint
Fugitive Emission Survey.	NA	Monthly
Visible Emission Survey.	NA	Monthly
Operation and Maintenance Plan.	NA	Maintain the current version on-site
Upset Log of all planned and unplanned excess emissions, as required by Condition G15.	NA	Per occurrence
40 CFR 60 Subpart Dc Recordkeeping		
The amount of natural gas combusted by each boiler.	Therms or MMCF	Monthly
The amount of fuel oil combusted by Emission Unit B-1.	Gallons	Monthly
Fuel oil supplier certifications for Emission Unit B-1.	NA	Each delivery of fuel oil
40 CFR 63 Subpart 6J Recordkeeping		
Total monthly and calendar year hours that the Emission Unit B-1 combusted fuel oil.	Hours	Monthly and calendar year
40 CFR 63 Subpart 6Q Recordkeeping		
Documentation that each wood preservative used does not use any chromium, arsenic, dioxins, or methylene chloride.	NA	Each wood preservative used

Reporting Requirements

34. The facility must submit to LRAPA the following reports by no later than the dates indicated in the table below: [LRAPA 34-016(2) and 42-0080(5)]

Report	Reporting Period	Due Date
Semiannual fuel oil report as required by 40 CFR 60 subpart Dc for Emission Unit Boiler B-1.	Semiannual	Postmarked by February 15, August 15
The upset log information required by Condition G13, if required by G13.	Annual	February 15
PSEL pollutant emissions as calculated according to Conditions 5	Annual	February 15

Report	Reporting Period	Due Date
and 6, including supporting calculations.		
GHG Report, if required by Condition 35.	Annual	March 31

35. The permittee must register and report in compliance with Chapter 340, Division 215 of the Oregon Administrative Rules, if the source's direct greenhouse gas emissions meet or exceed 2,500 metric tons CO₂e during the previous year. Once a source's direct greenhouse gas emissions meet or exceed 2,500 metric tons CO₂e during a year, the permittee must annually register and report in each subsequent year, regardless of the amount of the source's direct GHG emissions in future years, except as provided in OAR 340-215-0032 and OAR 340-215-0034. Air contamination sources required to register and report under OAR 340-215-0030(2) must register and submit annual emissions data reports to LRAPA under OAR 340-215-0044 by the due date for the annual report for non-greenhouse gas emissions specified in Condition 34, or by March 31 of each year, whichever is later. [LRAPA 34-016, OAR 340-215-0030(2) and 340-340-215-0046(1)(a)]
36. Unless otherwise specified, all reports, test results, notifications, etc., required by the above terms and conditions must be reported to the following office: [LRAPA 34-016]

Lane Regional Air Protection Agency
1010 Main Street
Springfield, Oregon 97477
(541) 736-1056

Outdoor Burning

37. Commercial and industrial outdoor burning is prohibited inside the Eugene and Springfield Urban Growth boundaries. Commercial and industrial outdoor burning is prohibited elsewhere, unless authorized pursuant to LRAPA 47-020. [LRAPA 47-015(4)&(5)]

Fee Schedule

38. In accordance with adopted regulations, the permittee will be invoiced for the annual permit fees on October 1st, with fees due December 1st of each year. [LRAPA 37-8020 Table 2]

JJW/CW
10/20/2023

GENERAL PERMIT CONDITIONS

General Conditions and Disclaimers

- G1. A copy of the permit application and this Air Contaminant Discharge Permit (ACDP) must be available on site for inspection upon request. [LRAPA 37-0020(3)]
- G2. The permittee must allow the Director or his/her authorized representatives access to the plant site and pertinent records at all reasonable times for the purpose of making inspections, surveys, collecting samples, obtaining data, reviewing and copying air contaminant discharge records and otherwise conducting necessary functions related to this permit in accordance with ORS 468.095. [LRAPA 13-020(1)(h)]
- G3. The issuance of this permit does not convey any property rights in either real or personal property, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of federal, state, or local laws or regulations.

Performance Standards and Emission Limits

- G4. The permittee must not cause or permit the deposition of any particulate matter which is larger than 250 microns in size at sufficient duration and quantity, as to create an observable deposition upon the real property of another person. [LRAPA 32-055]
- G5. The permittee must not discharge from any source whatsoever such quantities of air contamination which cause injury or damage to any persons, the public, business or property. Such determination to be made by LRAPA. [LRAPA 32-090(1)]
- G6. The permittee must not cause or permit emission of water vapor if the water vapor causes or tends to cause detriment to the health, safety or welfare of any person or causes, or tends to cause damage to property or business. [LRAPA 32-090(2)]
- G7. The permittee must not willfully cause or permit the installation or use of any device or use of any means which, without resulting in a reduction in the total amount of air contaminants emitted, conceals emissions of air contaminants which would otherwise violate LRAPA rules. [LRAPA 32-050(1)]
- G8. The permittee must not cause or permit the installation or use of any device or use of any means designed to mask the emissions of an air contaminant which causes or tends to cause detriment to health, safety or welfare of any person. [LRAPA 32-050(2)]
- G9. The permittee must not allow any materials to be handled, transported, or stored; or a building, its appurtenances or road(s) to be used, constructed, altered, repaired, or demolished; or any equipment to be operated, without taking reasonable precautions to prevent particulate matter from being airborne. [LRAPA 48-015(1)]
- G10. The permittee may not cause or allow air contaminants from any source subject to regulation by LRAPA to cause nuisance. [LRAPA 49-010(1)]

Excess Emissions: General Policy

- G11. Emissions of air contaminants in excess of applicable standards or permit conditions are unauthorized and are subject to enforcement action, pursuant to LRAPA 36-010 and 36-030.

These rules apply to any permittee operating a source which emits air contaminants in violation of any applicable air quality rule or permit condition, including but not limited to excess emissions resulting from the breakdown of air pollution control devices or operating equipment, process upset, startup, shutdown, or scheduled maintenance. Sources that do not emit air contaminants in excess of any applicable rule or permit condition are not subject to the recordkeeping and reporting requirements in LRAPA title 36. Emissions in excess of applicable standards are not excess emissions if the standard is in an NSPS or NESHAP and the NSPS or NESHAP exempts startups, shutdowns and malfunctions as defined in the applicable NSPS or NESHAP. [LRAPA 36-001(1)]

Excess Emissions: Notification and Record-keeping

- G12. For all other excess emissions not addressed in LRAPA Sections 36-010, 36-015, or 36-040, the following requirements apply: [LRAPA 36-020(1)]
- a. The owner or operator, of a small source, as defined by LRAPA 36-005(7), need not notify LRAPA of excess emissions events immediately unless otherwise required by permit condition, written notice by LRAPA, or if the excess emission is of a nature that could endanger public health.
 - b. Notification must be made to the LRAPA office. The current LRAPA telephone number during regular business hours (8 a.m. - 5 p.m., M-F) is (541) 736-1056. During nonbusiness hours, weekends, or holidays, the permittee must immediately notify LRAPA by calling the LRAPA Upset/Complaint Line. The current number is (541) 726-1930.
 - c. Follow-up reporting, if required by LRAPA, must contain all information required by Condition G15.
- G13. At each annual reporting period specified in this permit, or sooner if required by LRAPA, the permittee must submit a copy of the upset log entries for the reporting period, as required by Condition G15. [LRAPA 36-025(4)(a)]
- G14. Any excess emissions which could endanger public health or safety must immediately be reported to the Oregon Emergency Response System (OERS) at 1-800-452-0311.
- G15. The permittee must keep an upset log of all planned and unplanned excess emissions. The upset log must include the following: [LRAPA 36-025(3) and 36-030(1)]
- a. date and time each event was reported to LRAPA;
 - b. whether the process handling equipment and the air pollution control equipment were at all times maintained and operated in a manner consistent with good practice for minimizing emissions;
 - c. whether repairs or corrections were made in an expeditious manner when the permittee knew or should have known that emission limits were being or were likely to be exceeded;
 - d. whether the event was one in a recurring pattern of incidents which indicate inadequate design, operation, or maintenance; and
 - e. final resolution of the cause of the excess emissions.

Upset logs must be kept by the permittee for five (5) calendar years. [LRAPA 36-025(3)]

Excess Emissions: Scheduled Maintenance

- G16. If the permittee anticipates that scheduled maintenance of air contaminant sources or air pollution

control devices may result in excess emissions, the permittee must obtain prior LRAPA authorization of procedures that will be used to minimize excess emissions. Application for approval of procedures associated with the scheduled maintenance must be submitted and received by LRAPA in writing at least seventy-two (72) hours prior to the event. The application must include the following: [LRAPA 36-015(1)]

- a. reasons explaining the need for maintenance, including but not limited to: why the maintenance activity is necessary; why it would be impractical to shut down the source operation during the maintenance activity; if applicable, why air pollution control devices must be by-passed or operated at reduced efficiency during the maintenance activity; and why the excess emissions could not be avoided through better scheduling for maintenance or through better operation and maintenance practices;
 - b. identification of the specific production or emission control device or system to be maintained;
 - c. identification of the nature of the air contaminants likely to be emitted during the maintenance period, and the estimated amount and duration of the excess emissions, including measures such as the use of overtime labor and contract services and equipment that will be taken to minimize the length of the maintenance period; and
 - d. identification of specific procedures to be followed which will minimize excess emissions at all times during the scheduled maintenance.
- G17. No scheduled maintenance associated with the approved procedures in Condition G16 that is likely to result in excess emissions may occur during any period in which an Air Pollution Alert, Air Pollution Warning, or Air Pollution Emergency has been declared, or during an announced yellow or red woodstove advisory period, in areas determined by LRAPA as PM_{2.5} or PM₁₀ nonattainment areas. [LRAPA 36-015(6)]
- G18. In cases where LRAPA has not received notification of scheduled maintenance that is likely to cause excess emissions within the required seventy-two (72) hours prior to the event, or where such approval has not been waived pursuant to LRAPA 36-015(3), the permittee must immediately notify LRAPA by telephone of the situation, and must be subject to the requirements of Conditions G12 and G13. [LRAPA 36-015(7)]

Air Pollution Emergencies

- G19. The permittee must, upon declaration of an air pollution alert, air pollution warning, or air pollution emergency, take all emission reduction measures specified in Tables 1, 2, and 3 of LRAPA title 51. Permittees responsible for a source of air contamination within a Priority I AQCR must, upon declaration of an episode condition affecting the locality of the air contamination source, take all appropriate actions specified in the applicable table and must take all appropriate actions specified in an LRAPA-approved preplanned abatement strategy for such condition which has been submitted and is on file with LRAPA. [LRAPA 51-015]

Notification of Construction/Modification

- G20. The permittee must notify LRAPA in writing using an LRAPA "Notice of Intent to Construct" form, or other permit application forms and obtain approval in accordance with LRAPA 34-010 and 34-034 through 34-038 before:
- a. constructing, installing or establishing a new stationary source that will cause an increase in regulated pollutant emissions
 - b. making any physical change or change in the operation of an existing stationary source that will cause an increase, on an hourly basis at full production, in any regulated pollutant

- emissions; or
- c. constructing or modifying any pollution control equipment.

Notification of Name Change

G21. The permittee must notify LRAPA in writing, using an LRAPA Application for Administrative Amendment to ACDP form, within 60 days after legal change of the registered name of the company with the Corporation Division of the State of Oregon. [LRAPA 37-0030(4)]

Applicable administrative fees must be submitted with an application for the name change.

Permit Renewal

G22. Application for renewal of this permit must be submitted not less than 120 days prior to the permit expiration date for Simple ACDPs, and 180 days prior to the permit expiration date for Standard ACDP. [LRAPA 37-0040(2)(b)]

G23. A source may not be operated after the expiration date of a permit, unless any of the following occur prior to the expiration date of the permit: [LRAPA 37-0082(1)(a)]

- a. A timely and complete application for renewal or for an LRAPA Title V Operating Permit has been submitted; or
- b. Another type of permit, ACDP or Title V, has been issued authorizing operation of the source.

G24. For a source operating under an ACDP or LRAPA Title V Operating Permit, a requirement established in an earlier ACDP remains in effect notwithstanding expiration of the ACDP, unless the provision expires by its terms or unless the provision is modified or terminated according to the procedures used to establish the requirement initially. [LRAPA 37-0082(1)(c)]

G25. Any permittee who fails to submit any relevant facts or who has submitted incorrect information in a permit application must, upon becoming aware of such failure or incorrect submittal, promptly submit such supplementary facts or corrected information. [LRAPA 37-0040(4)]

Termination Conditions

G26. This permit will be automatically terminated upon: [LRAPA 37-0082(2)]

- a. Issuance of a renewal or new ACDP for the same activity or operation;
- b. Written request of the permittee, if LRAPA determines that a permit is no longer required;
- c. Failure to submit a timely application for permit renewal. Termination is effective on the permit expiration date; or;
- d. Failure to pay annual fees within 90 days of invoice by LRAPA, unless prior arrangements for payment have been approved in writing by LRAPA.

G27. If LRAPA determines that a permittee is in noncompliance with the terms of the permit, submitted false information in the application or other required documentation, or is in violation of any applicable rule or statute, LRAPA may revoke the permit. LRAPA will provide notice of the intent to revoke the permit to the permittee under LRAPA title 31. The notice will include the reasons why the permit will be revoked, and include an opportunity for the permittee to request a contested case hearing prior to the revocation. A written request for hearing must be received by LRAPA within 60 days from service of the notice on the permittee, and must state the grounds of

the request. The hearing will be conducted as a contested case hearing under ORS 183.413 through 183.470 and LRAPA title 14. The permit will continue in effect until the 60th day after service of the notice on the permittee, if the permittee does not timely request a hearing, or until a final order is issued if the permittee timely requests a hearing. [LRAPA 37-0082(4)(a)]

- G28. A permit automatically terminated under LRAPA 37-0082(2)(b) through (2)(d) may only be reinstated by the permittee by applying for a new permit. The permittee must also pay the applicable new source permit application fees in this title unless the owner or operator submits the renewal application within three months of the permit expiration date. [LRAPA 37-0082(3)]
- G29. If LRAPA finds there is a serious danger to the public health, safety or the environment caused by a permittee's activities, LRAPA may immediately revoke or refuse to renew the permit without prior notice or opportunity for a hearing. If no advance notice is provided, notification will be provided to the permittee as soon as possible as provided under LRAPA title 31. The notification will set forth the specific reasons for the revocation or refusal to renew and will provide an opportunity for the permittee to request a contested case hearing for review of the revocation or refusal to renew. A permittee's written request for hearing must be received by LRAPA within 90 days of service of the notice on the permittee and must state the grounds for the request. The hearing will be conducted as a contested case hearing under ORS 183.413 through 183.470 and LRAPA title 14. The revocation or refusal to renew becomes final without further action by LRAPA if a request for a hearing is not received within the 90 days. If a request for a hearing is timely received, the revocation or refusal to renew will remain in place until issuance of a final order. [LRAPA 37-0082(4)(b)]
- G30. Any hearing requested must be conducted pursuant to the rules of LRAPA. [LRAPA title 14]

Asbestos

- G31. The permittee must comply with the asbestos abatement requirements in LRAPA title 43 for all activities involving asbestos-containing materials, including, but not limit to, demolition, renovation, repair, construction, and maintenance. [LRAPA title 43]

[Revised 1/19/18]

LIST OF ABBREVIATIONS THAT MAY BE USED IN THIS PERMIT

ACDP	Air Contaminant Discharge Permit		hazardous air pollutants
AQMA	Air Quality Management Area	MM	Million
ACS	Applied coating solids	MMBtu	Million British thermal units
Act	Federal Clean Air Act	MMCF	Million cubic feet
ASTM	American Society of Testing and Materials	NA	Not applicable
BDT	Bone dry ton	NESHAP	National Emission Standards for Hazardous Air Pollutants
Btu	British thermal unit	NOx	Nitrogen oxides
CAM	Compliance Assurance Monitoring	NSPS	New Source Performance Standards
CAO	Cleaner Air Oregon	NSR	New Source Review
CD ID	Control device identifier	O2	Oxygen
CEMS	Continuous Emissions Monitoring System	OAR	Oregon Administrative Rules
CFR	Code of Federal Regulations	ODEQ	Oregon Department of Environmental Quality
CI	Compression Ignition	OPR	Operation
CMS	Continuous Monitoring System	ORS	Oregon Revised Statutes
CO	Carbon Monoxide	O&M	Operation and maintenance
CO2	Carbon dioxide	SB	Lead
CO2e	Carbon dioxide equivalent	PCD	Pollution Control Device
COMS	Continuous Opacity Monitoring System	PM	Particulate matter
CPDS	Certified Product Data Sheet	PM2.5	Particulate matter less than 2.5 microns in size
CPMS	Continuous parameter monitoring system	PM10	Particulate matter less than 10 microns in size
DEQ	Department of Environmental Quality	ppm	Parts per million
dscf	Dry standard cubic feet	PSEL	Plant Site Emission Limit
EF	Emission factor	psia	pounds per square inch, actual
EPA	US Environmental Protection Agency	PTE	Potential to Emit
EU	Emissions Unit	QIP	Quality Improvement Plan
EU ID	Emission unit identifier	RICE	Reciprocating Internal Combustion Engine
FCAA	Federal Clean Air Act	SACC	Semi-Annual Compliance Certification
ft2	Square foot	SCEMP	Surrogate Compliance Emissions Monitoring Parameter
FSA	Fuel sampling and analysis	Scf	Standard cubic foot
gal	Gallon	SDS	Safety data sheet
GHG	Greenhouse Gas	SER	Significant emission rate
gr/dscf	Grain per dry standard cubic feet (1 pound = 7000 grains)	SERP	Source emissions reduction plan
HAP	Hazardous Air Pollutants as defined by LRAPA title 12	SI	Spark Ignition
HCFC	Halogenated Chlorofluorocarbons	SIC	Standard Industrial Code
Hr	Hour	SIP	State Implementation Plan
ID	Identification number or label	SO2	Sulfur dioxide
I&M	Inspection and maintenance	ST	Source test
Lb	Pound	TAC	Toxic air contaminant
LRAPA	Lane Regional Air Protection Agency	TACT	Typically Achievable Control Technology
MACT	Maximum Achievable Control Technology	TEU	Toxic Emission Unit
MBF	Thousand board feet	TPY	Tons per year
MERV	Minimum efficiency reporting values	VE	Visible emissions
MFHAP	Metal fabrication or finishing metal	VMT	Vehicle miles traveled
		VOC	Volatile organic compounds
		Year	A period consisting of any 12-

McFarland Cascade Pole & Lumber Company
Permit No. 205108
Expiration Date: November 10, 2025
Modified Date: [INSERT DATE]

Page 15 of 14

consecutive calendar month